

Admin

Get *parameter* (see Set parameters) AHDBU
 Set Security|Timeout *value* A

Antivirus

Count *pattern* A
 Get *vendor parameter* (see Set parameters) A
 GetMessage *vendor messagepart* A
 GetVersion *vendor* A
 List *pattern* A
 Set *vendor* AdminMessage|NotifyAdmin *value* A
 Set *vendor* NotifyRecipient|NotifySender *value* A
 Set *vendor* QuarantineAddress|QuarantineDelay *value* A
 Set *vendor* RecipientMessage|ScanList *value* A
 Set *vendor* SenderMessage|VirusAction *value* A
 SetMessage *vendor messagepart value* A
 Update *vendor* A

Auth

Count AB
 Get *parameter* (see Set parameters) AB
 List AB
 Set Default|PassChars|PassMin *value* A

Autoreply

Clear *username* AHDU
 Get *username* AHDBU
 GetExpiration *username* AHDU
 GetInterval *username* AHDBU
 GetMode *mode* AHD
 GetStart *username* AHDU
 Set *username* AHDU
 SetExpiration *username datestring* AHDU
 SetInterval *username interval* AHD
 SetMode *mode state* AHD
 SetStart *username datestring* AHDU

Backup

Abort *jobid* AB
 Full *device blocksize* AB
 Get MailboxPath *value* A
 Incremental *device blocksize* AB
 LevelX *device blocksize* AB
 Media *keyword jobid* AB
 Selective *device blocksize mailboxes* AB
 Status AB

Brand

Add *brandname URL* A
 Assign *domain brandname* A
 Assigned *domain* A
 Change *brandname URL* A
 Count *pattern* A
 CountDomain *pattern* A
 Delete *brandname* A
 Get *brandname URL* A
 List *pattern* A
 ListDomain *pattern* A

Calendar

AddSubscribed *calname title type* AHDB
 CountSubscribed *pattern* AHDB
 DeleteSubscribed *calname* AHDB
 DownSync *calname protocol* AHDBU
 ExportCal *calname* AHDBU
 Get *parameter* (see Set parameters) AHDBU
 ImportCal *calname value* AHDBU
 ListSubscribed *pattern* AHDB
 Set AttachEnabled|AttachQuota *value* AD
 Set DayGranularity|DfltCalFlags|DfltDayEnd *value* AD
 Set DfltDayStart|DfltUiFlags|DfltView *value* AD
 Set ExternalMaxNum|ExternalMaxSize *value* AD
 Set GroupCalMode|LdapMaxCount|LdapTimeout *value* AD
 Set MaxIdleConnections|MaxIdleUser *value* AD
 Set MaxNumEvents *value* AD
 Set MonthlySummaryDay|MonthlySummaryTime *value* AD
 Set PagerReminderDiff|ReminderDiff *value* AD
 Set RemoveAfter|ResourceGroup *value* AD
 Set ScheduleMode *value* AD
 Set SummaryTimeEmail|SummaryTimePager|Timeout *value* AD
 Set WeeklySummaryDay|WeeklySummaryTime *value* AD
 UpSync *calname protocol options value* AHDBU

Keywords separated by | are alternatives.

Roles:

A = Administrator ■ H = Helpdesk administrator ■ D = Domain administrator
 B = Backup operator ■ U = User

For detailed information about these commands:

Telnet to your Mirapoint system, log in as an administrator, and type Help.

COMMAND QUICK REFERENCE

Cluster

Add <i>clustername</i>	A
Attach <i>clustername</i>	A
Count <i>pattern</i>	A
CountMember <i>clustername pattern</i>	A
Delete	A
Detach	A
Get Name Role Status <i>value</i>	A
List <i>pattern</i>	A
ListMember <i>clustername pattern</i>	A
Scan	A

Conf

Count	AB
Disable <i>feature</i>	A
Enable <i>feature</i>	A
Enabled <i>feature</i>	AHB
Export <i>nothing confdata</i>	A
Get HttpProxy	A
Import <i>nothing confdata</i>	A
List	AB
Set HttpProxy <i>value</i>	A

Cos

Disable <i>feature</i>	A
Enable <i>feature</i>	A
Enabled <i>feature</i>	AHB
GetStatus <i>username pattern</i>	AH
List <i>pattern</i>	AHB

Customercare

Get Contact	AB
Set Contact <i>value</i>	A

Diag

Abort	A
Changer Inquiry "" "" "" ""	A
Clear TapeDeviceLog	A
Disk Inquiry <i>logicalID</i>	A
Get ChangerAddress DataXferElementAddr	A
Get TapeAddress TapeCompression TapeCompressionRatio	A
NetStat <i>pattern</i>	A
Ping <i>host packetcount</i>	A
Rescan	A
Set TapeCompression <i>value</i>	A
SmtPConnect <i>from.Addr to.Addr remoteSmtP[:port] options</i>	A
Status	A
Tape <i>program numrecords times blocksize</i>	A
TcpTraceRoute <i>host portnum</i>	A
TraceRoute <i>host</i>	A

Dir

AddACL <i>dbname aclname what</i>	A
AddAclEntry <i>dbname aclname entry who level control</i>	A
AddDb <i>dbname args</i>	A
AddDbSuffix <i>dbname DN</i>	A
AddIndex <i>dbname attribute types</i>	A
AddRepHost <i>raname URL</i>	A
AddReplica <i>raname type masterbase slavebase</i>	A
AddSchema <i>schemaname value</i>	A
CountACL <i>dbname pattern</i>	AB
CountAclEntry <i>dbname aclname pattern</i>	AB
CountDb <i>pattern</i>	AB
CountDbOption <i>dbname pattern</i>	AB
CountDbSuffix <i>dbname pattern</i>	AB
CountIndex <i>dbname pattern</i>	AB
CountRepHost <i>raname pattern</i>	AB
CountRepOption <i>raname pattern</i>	AB
CountReplica <i>pattern</i>	AB
CountSchema <i>pattern</i>	AB
DeleteACL <i>dbname aclname</i>	A
DeleteAclEntry <i>dbname aclname entry</i>	A
DeleteDb <i>dbname</i>	A
DeleteDbSuffix <i>dbname DN</i>	A
DeleteIndex <i>dbname attribute</i>	A

Parameters enclosed by [and] are optional.
Keywords separated by | are alternatives.

Roles:

A = Administrator ■ H = Helpdesk administrator ■ D = Domain administrator
B = Backup operator ■ U = User

For detailed information about these commands:
Telnet to your Mirapoint system, log in as an administrator, and type Help.

COMMAND QUICK REFERENCE

Dir (continued)

DeleteRepHost <i>raname URL</i>	A
DeleteReplica <i>raname</i>	A
DeleteSchema <i>schemaname</i>	A
ExportConfig <i>arg</i>	AB
ExportLdif <i>suffix flag</i>	A
Get <i>option</i>	AB
GetAcl <i>dbname aclname</i>	AB
GetAclEntry <i>dbname aclname entry</i>	AB
GetDbOption <i>dbname option</i>	AB
GetIndex <i>dbname attribute</i>	AB
GetLogging <i>logtype</i>	AB
GetRepOption <i>raname option</i>	AB
GetSchema <i>schemaname</i>	AB
ImportConfig <i>arg value</i>	A
ImportLdif <i>suffix database flag value</i>	A
ListAcl <i>dbname pattern</i>	AB
ListAclEntry <i>dbname aclname pattern</i>	AB
ListDb <i>pattern</i>	AB
ListDbOption <i>dbname pattern</i>	AB
ListDbSuffix <i>dbname pattern</i>	AB
ListIndex <i>dbname pattern</i>	AB
ListRepHost <i>raname pattern</i>	AB
ListRepOption <i>raname pattern</i>	AB
ListReplica <i>pattern</i>	AB
ListSchema <i>pattern</i>	AB
ModifyLdif <i>suffix flag value</i>	A
Promote <i>raname URL</i>	A
Replicate <i>raname URL protocol</i>	A
RepStat <i>raname URL</i>	A
Set <i>option value</i>	A
SetAcl <i>dbname aclname what</i>	A
SetAclEntry <i>dbname aclname entry who level control</i>	A
SetDbOption <i>dbname option value</i>	A
SetIndex <i>dbname attribute types</i>	A
SetLogging <i>logtype level</i>	A
SetRepOption <i>raname option value</i>	A
SetSchema <i>schemaname value</i>	A

DI

Add <i>distlist</i>	AHD
Count	AHDB
Delete <i>distlist</i>	AHD
ImportSendMail <i>aliases</i>	AHD
List	AHDB
Membership [<i>dl-name</i>]	AHDBU

Dlentry

Add <i>distlist member</i>	AHD
AddBulk <i>distlist members</i>	AHD
Count <i>distlist</i>	AHDB
Delete <i>distlist member</i>	AHD
List <i>distlist</i>	AHDB

Dns

Add <i>nameserver</i>	A
AddHost <i>hostname ipaddr</i>	A
Count	AB
CountHost	A
Delete <i>nameserver</i>	A
DeleteHost <i>hostname</i>	A
FlushCache	A
Get Domain	AB
List	AB
ListHost	A
Lookup <i>name options</i>	A
Set Domain <i>value</i>	A

Domain

Add <i>domain-name</i>	A
Count <i>pattern</i>	AHB
Delete <i>domain-name</i>	A
Get <i>parameter domain-name</i> (see Set parameters)	AHDB
GetCurrent	AHB
List <i>pattern</i>	AHB
Set Autoreplies <i>domain-name value</i>	AHD
Set Calendar.MaxNumEvents <i>domain-name value</i>	AHD
Set Calendar.RemoveAfter <i>domain-name value</i>	AHD
Set Calendar.Timeout <i>domain-name value</i>	AHD
Set CatchAll DiskQuota DIs <i>domain-name value</i>	AHD
Set Fwds Signature UserQuota <i>domain-name value</i>	AHD
SetCurrent <i>domain-name</i>	AHB

Exception

Add <i>protocol attribute domain value</i>	A
Count <i>protocol attribute pattern</i>	AB
CountAttr <i>protocol pattern</i>	AB
CountProtocols <i>pattern</i>	AB
Delete <i>protocol attribute domain</i>	AHDBU
List <i>protocol attribute pattern</i>	AB
ListAttr <i>protocol pattern</i>	AB
ListProtocols <i>pattern</i>	AB
Test <i>domain IPaddress protocol attribute constraint</i>	AB

Parameters enclosed by [and] are optional.
Keywords separated by | are alternatives.

Roles:

A = Administrator ■ H = Helpdesk administrator ■ D = Domain administrator
B = Backup operator ■ U = User

For detailed information about these commands:
Telnet to your Mirapoint system, log in as an administrator, and type Help.

COMMAND QUICK REFERENCE

Failover

AddPort <i>portnum monaddr</i>	A
CountPort <i>pattern</i>	A
DeletePort <i>portnum</i>	A
Get <i>parameter</i>	A
ListPort <i>pattern</i>	A
Reboot <i>unit</i>	A
Set <i>parameter value</i>	A
Shutdown <i>unit</i>	A

Filter

Add <i>scope fname action arg any-all stop-go rules</i>	AH DU
Change <i>scope fname action arg any-all stop-go rules</i>	AH DU
Clear <i>scope</i>	AH DU
Count <i>scope</i>	AH DBU
Delete <i>scope fname</i>	AH DU
Export <i>scope</i>	AH DBU
Fetch <i>scope fname</i>	AH DBU
Get RemovedAttachmentsMessage	AD
Import <i>scope filterset</i>	AH DU
List <i>scope</i>	AH DBU
Move <i>scope fname position</i>	AH DU
Set RemovedAttachmentsMessage <i>value</i>	AD
Test <i>scope testmbx</i>	AH DU

Fwd

Clear <i>username</i>	AH DU
Get <i>username</i>	AH DBU
Set <i>username address keepcopy</i>	AH DU

Getmail

Add <i>username nickname server uid password options</i>	AH DU
Change <i>username nickname server uid password options</i>	AH DU
Check <i>username pattern</i>	AH DU
Count <i>username pattern</i>	AH DU
Delete <i>username nickname</i>	AH DU
Get MinPoll	A
List <i>username pattern</i>	AH DU
ListBackup <i>username pattern</i>	AH DU
Rename <i>username oldname nickname</i>	AH DU
Set MinPoll <i>value</i>	A

Halt

A

Help

<i>topic</i>	AH DBU
--------------	--------

Http

Get <i>parameter</i> (see Set parameters)	AB
Set Cookies LdapRouteUrls MaxConnections <i>value</i>	A
Set MaxDirectoryTraversals MaxHeaderLength <i>value</i>	A
Set MaxRequestBodySize MaxTotalHeaderSize <i>value</i>	A
Set Mode ProxyTimeout Root Security <i>value</i>	A

Imap

Get <i>parameter</i> (see Set parameters)	AB
Set Mode NameSpace ProxyCapability <i>value</i>	A
Set QuotaWarn Security Timeout <i>value</i>	A

Kerb5

Add <i>host</i>	A
Count	AB
Delete <i>host</i>	A
Get <i>parameter</i> (see Set parameters)	AB
List	AB
Set Realm Srvtab <i>value</i>	A

Key

Count <i>type</i>	AB
Delete <i>type interface</i>	A
Get <i>type interface</i>	AB
GetPublic <i>type interface</i>	AB
List <i>type</i>	A
New <i>type interface hostname arguments</i>	A
Set <i>type interface key</i>	A

Parameters enclosed by [and] are optional.
Keywords separated by | are alternatives.

Roles:

A = Administrator ■ H = Helpdesk administrator ■ D = Domain administrator
B = Backup operator ■ U = User

For detailed information about these commands:
Telnet to your Mirapoint system, log in as an administrator, and type Help.

COMMAND QUICK REFERENCE

Ldap

Add <i>server-spec</i>	A
AddAccess <i>baseDN bindDN passwd passwd-type</i>	A
AddMailHost <i>domain mailhost</i>	A
AddQuarantineHost <i>domain mailhost</i>	A
Count	AHB
CountAccess <i>pattern</i>	AB
CountMailhost <i>pattern</i>	AB
CountObjClass <i>pattern</i>	AB
CountQuarantineHost <i>pattern</i>	AB
CountQueries	AB
Delete <i>server-spec</i>	A
DeleteAccess <i>baseDN</i>	A
DeleteMailHost <i>domain</i>	A
DeleteQuarantineHost <i>domain</i>	A
FlushCache <i>table key</i>	A
Get <i>parameter</i> (see Set parameters)	AHB
GetAccess <i>baseDN</i>	AB
GetMailHost <i>jmmDomain</i>	AB
GetObjClass <i>ocspec</i>	AB
GetQuarantineHost <i>jmmDomain</i>	AB
GetQuery <i>queryspec</i>	AB
List <i>pattern</i>	AHB
ListAccess <i>pattern</i>	AB
ListMailHost <i>pattern</i>	AB
ListObjClass <i>pattern</i>	AB
ListQuarantineHost <i>pattern</i>	AB
ListQueries	AB
Search <i>server-spec basedn filter attrs options</i>	A
Set AutoProvision CacheTimeout Ldif <i>value</i>	A
Set LocalCosTable Mirabase <i>value</i>	A
Set SubDomainRoutingLevel <i>value</i>	A
SetObjClass <i>ocspec objclass</i>	A
SetQuery <i>queryspec basedn filter attr type</i>	A
TestQuery <i>queryspec args</i>	A

License

Apply <i>key</i>	A
Count <i>pattern</i>	A
Fetch	A
HostId	A
List <i>pattern</i>	A
Override <i>key hostid</i>	A
Revoke <i>key</i>	A
Status	A

Locale

Count	AB
Get <i>parameter</i> (see Set parameters)	AB
List	AB
Set Default LoginFooter Unannounced <i>value</i>	A

Log

AddRoute <i>routingname identifierSet method meth.Args</i>	A
CountRoutes <i>pattern</i>	AB
DeleteRoute <i>routingname</i>	A
DiagWatch <i>identifierSet</i>	A
Get <i>parameter</i> (see Set parameters)	AB
ListRoutes	AB
Set History MarkInterval SyncInterval <i>value</i>	A
Watch <i>identifierSet sequencing</i>	AB

Logout

AHDBU

Mailbox

Add <i>mbname</i>	AH DU
Copy <i>src host srcmbx srcuser srcpass destmbx</i>	AH DU
Count <i>pattern</i>	AH DBU
Delete <i>mbname</i>	AH DU
Get <i>parameter</i> (see Set parameters)	AH DB
GetAcl <i>mbname</i>	AH DBU
List <i>pattern</i>	AH DBU
MsgExpireNow <i>criteria limit</i>	A
Publish <i>domains folders</i>	A
Rename <i>oldname newname</i>	AH DU
Set Broadcast UndeleteQuota <i>value</i>	A
SetAcl <i>mbname user permissions</i>	AH DU
Sync <i>domains folders</i>	A
Undelete mailbox	AU

Maildom

Add <i>mail-domain</i>	A
Count <i>pattern</i>	AB
Delete <i>mail-domain</i>	A
List <i>pattern</i>	AB

Mailq

Count <i>pattern</i>	A
Delete <i>pattern</i>	A
Get <i>msg-part queue-id</i>	A
List <i>pattern</i>	A
Reject <i>pattern reason</i>	A
Retryall	A
Transfer <i>pattern host-or-IP</i>	A

Parameters enclosed by [and] are optional.
Keywords separated by | are alternatives.

Roles:

A = Administrator ■ H = Helpdesk administrator ■ D = Domain administrator
B = Backup operator ■ U = User

For detailed information about these commands:
Telnet to your Mirapoint system, log in as an administrator, and type Help.

COMMAND QUICK REFERENCE

Message

Count <i>localepattern facilitypattern</i>	ADB
CountArgs <i>locale facility variable</i>	ADB
CountFacilities <i>pattern</i>	ADB
CountPolicies <i>locale facility</i>	ADB
ExportStrings <i>arg</i>	AB
Get <i>locale facility</i>	ADB
GetArg <i>locale facility variable</i>	ADB
GetPolicy <i>locale facility</i>	ADB
GetString <i>name</i>	AB
ImportStrings <i>arg value</i>	AB
List <i>localepattern facilitypattern</i>	ADB
ListArgs <i>locale facility variable</i>	ADB
ListFacilities <i>pattern</i>	ADB
ListPolicies <i>locale facility</i>	ADB
Send <i>locale facility dest.Addr arguments</i>	ADB
Set <i>locale facility message</i>	ADB
SetArg <i>locale facility variable value</i>	ADB
SetPolicy <i>locale facility value</i>	ADB
SetString <i>name value</i>	AB

Migrate

Cancel	A
CheckSwitch	A
Clear	A
Finalize	A
From <i>source</i>	A
Get <i>parameter</i> (see Set parameters)	A
Restart	A
Set RetryCount RetryDelay BandwidthLimit <i>value</i>	A
Status	A
Switchover	A
Sync	A
To <i>target</i>	A
Version	A

Model

Get AppType Chassis Compliance CPU	AB
Get Enet Info Mem Raid Serial Storage	AB

Mon

Clear	A
Disable NetMonPing	A
Enable NetMonPing	A
Enabled NetMonPing	A
GetThresh <i>parameter</i> (see SetThresh parameters)	AB
SetThresh System.ADMINC <i>value</i>	A
SetThresh System.DNS*RESP <i>value</i>	A
SetThresh System.IMAPC <i>value</i>	A
SetThresh System.KERB4*RESP <i>value</i>	A
SetThresh System.KERB5*RESP <i>value</i>	A
SetThresh System.LDAP*RESP <i>value</i>	A
SetThresh System.LMRRESP <i>value</i>	A
SetThresh System.LOAD <i>value</i>	A

Mon (continued)

SetThresh System.NTP*RESP <i>value</i>	A
SetThresh System.OMRRESP <i>value</i>	A
SetThresh System.POPC <i>value</i>	A
SetThresh System.RADIUS*RESP <i>value</i>	A
SetThresh System.RBL*RESP <i>value</i>	A
SetThresh System.ROUTERRESP <i>value</i>	A
SetThresh System.SMTPC <i>value</i>	A
Status	A

Mtaverify

Add <i>host-spec</i>	A
AddMisbehavingMailer <i>IPAddr/netmask</i>	A
AddReverseMxException <i>exception</i>	A
Count <i>pattern</i>	AHB
CountMisbehavingMailer <i>pattern</i>	A
Delete <i>host-spec</i>	A
DeleteMisbehavingMailer <i>IPAddr/netmask</i>	A
DeleteReverseMxException <i>exception</i>	A
Export <i>destination</i>	A
ExportReverseMxList	A
Flush <i>type</i>	A
Get <i>parameter</i> (see Set parameters)	AHB
Import <i>source value</i>	A
ImportReverseMxList <i>list</i>	A
List <i>pattern</i>	AHB
ListMisbehavingMailer <i>pattern</i>	A
Set AllowedEntryLifetime AllowEntireIp <i>value</i>	A
Set AllowMisbehavingMailers <i>value</i>	A
Set AllowNullFrom AllowRelays <i>value</i>	A
Set CheckSuspectList ExemptOnSpf IgnoreRecipients <i>value</i>	A
Set InboundOnly InitialEntryLifetime <i>value</i>	A
Set InitialTimeout ReverseMx <i>value</i>	A
Test <i>IPaddress sender recipient</i>	AHB

Parameters enclosed by [and] are optional.
Keywords separated by | are alternatives.

Roles:

A = Administrator ■ H = Helpdesk administrator ■ D = Domain administrator
B = Backup operator ■ U = User

For detailed information about these commands:

Telnet to your Mirapoint system, log in as an administrator, and type Help.

COMMAND QUICK REFERENCE

Ndmp

Clear Logprotocol	A
DeleteTs <i>backupType backupLevel</i>	AB
EstimateSize <i>backupType backupLevel</i>	AB
Export Logprotocol <i>destination</i>	AB
Get SoftwareVersion (also see Set parameters)	AB
GetTs <i>backupType backupLevel</i>	AB
Merge <i>action</i>	A
Set DirOnly Dma LogProtocol <i>value</i>	A
Set Port PreferredIp Version <i>value</i>	A

Netif

AddAlias <i>portnum IPAddr/mask-bits</i>	A
AddLogical <i>logicalPort type</i>	A
AddRoute <i>destIPAddr/mask-bits gatewayIPAddr options</i>	A
AddTrustedIp <i>IPAddr</i>	A
Bind <i>portnum IPAddr/mask-bits</i>	A
Bindings	A
BindLogical <i>logicalPort physicalPort</i>	A
CountAliases <i>portnum</i>	A
CountLogical	A
CountMedia <i>pattern</i>	A
CountRoutes <i>pattern</i>	A
CountTrustedIp <i>pattern</i>	A
DeleteAlias <i>portnum IPAddr</i>	A
DeleteLogical <i>logicalPort</i>	A
DeleteRoute <i>destinationIPAddr/mask-bits</i>	A
DeleteTrustedIp <i>IPAddr</i>	A
Get <i>parameter portnum</i> (see Set parameters)	A
GetDomain <i>IPAddr</i>	A
GetLogical <i>parameter logicalPort</i>	A
ListAliases <i>portnum</i>	A
ListLogical <i>pattern</i>	A
ListMedia <i>pattern</i>	A
ListRoutes <i>pattern</i>	A
ListTrustedIp <i>pattern</i>	A
Set BlackholeDuration <i>portnum setting</i>	A
Set LimitTcpConnectCount <i>portnum setting</i>	A
Set LimitTcpConnectRate <i>portnum setting</i>	A
Set MaxTcpConnectCount <i>portnum setting</i>	A
Set MaxTcpConnectRate <i>portnum setting</i>	A

Netif (continued)

Set Media PrimaryPort <i>portnum setting</i>	A
SetDomain <i>IPAddr domainName</i>	A
SetLogical ArpMon ArpMonAddr <i>logicalPort value</i>	A
SetLogical Failover LinkDownDelay <i>logicalPort value</i>	A
SetLogical LinkMon LinkUpDelay Mode <i>logicalPort value</i>	A
Unbind <i>portnum</i>	A
UnbindLogical <i>logicalPort physicalPort</i>	A

Ntdm

Add <i>ntdomain host:port</i>	A
Count <i>ntdomain pattern</i>	AB
Delete <i>ntdomain host:port</i>	A
Export	A
GetDefaultDomain	AB
Import <i>URL value</i>	A
List <i>ntdomain pattern</i>	AB
ListDomain <i>pattern</i>	AB
SetDefaultDomain <i>ntdomain</i>	A

Ntp

Add <i>ntp host</i>	A
Count	AB
Delete <i>ntp host</i>	A
Get Date KnownZones Status Zone	AB
List	AB
Set Date Zone <i>value</i>	A
Synchronize <i>ntp host</i>	A

Patternlist

Count <i>pattern</i>	AHDB
Delete <i>listname</i>	AHD
Export <i>listname</i>	AHDB
Import <i>listname patternlist</i>	AHD
List <i>pattern</i>	AHDB

Pop

Get <i>parameter</i> (see Set parameters)	AB
Set Auth Mode MinPoll Security Timeout <i>value</i>	A

Quota

Get Storage <i>mailbox</i>	AHDBU
GetPolicy <i>parameter</i> (see SetPolicy parameters)	AHD
Set Storage <i>mailbox value</i>	AHD
SetPolicy DefaultSendOverQuotaMessage <i>value</i>	AHD
Setpolicy OverQuota <i>value</i>	AHD
Setpolicy OverQuotaMessage <i>value</i>	AHD
Setpolicy SendOverQuotaMessage <i>value</i>	AHD

Parameters enclosed by [and] are optional.
Keywords separated by | are alternatives.

Roles:

A = Administrator ■ H = Helpdesk administrator ■ D = Domain administrator
B = Backup operator ■ U = User

For detailed information about these commands:
Telnet to your Mirapoint system, log in as an administrator, and type Help.

COMMAND QUICK REFERENCE

Radius

Add <i>host</i>	A
Count	AB
Delete <i>host</i>	A
Get <i>parameter</i> (see Set parameters)	AB
List <i>pattern</i>	AB
Set Secret SendUserNameAsTyped Timeout <i>value</i>	A

Reboot

A

Relay

Add <i>relay</i>	A
Count	AB
Delete <i>relay</i>	A
List <i>pattern</i>	AB

Replicate

Cancel	A
CheckSwitch	A
Clear	A
Finalize	A
From <i>masterHost</i>	A
Get <i>parameter</i> (see Set parameters)	A
Restart	A
Set RetryCount RetryDelay BandwidthLimit <i>value</i>	A
Status	A
SwitchOver	A
Sync	A
To <i>replicaHost</i>	A
Version	A

Reputation

AddFixed <i>cidr rep</i>	A
CountFixed <i>pattern</i>	A
DeleteFixed <i>cidr</i>	A
GetAction <i>rep</i>	A
GetDelay <i>rep</i>	A
ListFixed <i>pattern</i>	A
Query <i>ip-address</i>	A
SetAction <i>rep "action-list"</i>	A
SetDelay <i>rep seconds</i>	A
Update <i>key</i>	A

Restore

Abort <i>jobid</i>	A
All <i>device options</i>	A
Media <i>keyword jobid</i>	A
Selective <i>device blocksizes mailboxes</i>	A
Status	A

Role

Add <i>role user</i>	AD
Count <i>role</i>	ADB
Delete <i>role user</i>	AD
List <i>role</i>	ADB

Schedule

Add <i>schedname frequency datespec</i>	A
Count <i>pattern</i>	AHB
Delete <i>schedname</i>	A
GetCommand <i>schedname</i>	AHB
GetString <i>schedname</i>	AHB
GetFrequency <i>schedname</i>	AHB
List <i>pattern</i>	AHB

Service

Disable <i>service</i>	A
Enable <i>service</i>	A
Enabled <i>service</i>	AB
ListServices	A
Restart <i>service</i>	A
Start <i>service</i>	A
Started <i>service</i>	A
Stop <i>service</i>	A

Parameters enclosed by [and] are optional.
Keywords separated by | are alternatives.

Roles:

A = Administrator ■ H = Helpdesk administrator ■ D = Domain administrator
B = Backup operator ■ U = User

For detailed information about these commands:

Telnet to your Mirapoint system, log in as an administrator, and type Help.

COMMAND QUICK REFERENCE

SmtP

AddListener <i>listenerSpec</i>	AB
AddRblHost <i>hostname</i>	A
AddrTest <i>address</i>	AH
CountListener <i>pattern</i>	AB
CountRblHost	AH
DeleteListener <i>listenerSpec</i>	AB
DeleteRblHost <i>hostname</i>	A
DisableListener <i>listenerSpec</i>	AB
EnableListener <i>listenerSpec</i>	AB
FlushLoginBeforeSmtP	A
Get <i>parameter</i> (see Set parameters)	AHB
HostStat <i>host</i>	A
ListListener <i>pattern</i>	AB
ListRblHost <i>pattern</i>	AH
Set BannerDelay BannerDelayTime <i>value</i>	AHB
Set ConnectPort CustomerErrorString <i>value</i>	AHB
Set DisplayMosVersion DsnDisable DsnLimit <i>value</i>	AHB
Set DsnLimit DsnRetryCnt <i>value</i>	AHB
Set Fastpath IdentHost LdapMasqSender <i>value</i>	AHB
Set LdapRouting LdapMxRouting ListenPort <i>value</i>	AHB
Set Lmr LoginBeforeSmtP LoginBeforeSmtPServer <i>value</i>	AHB
Set LoginBeforeSmtPTime MailReturn MailWarn <i>value</i>	AHB
Set Masq MaxMsg MaxMsgCnt MaxMsgSum <i>value</i>	AHB
Set MaxRecip MtaVerify NoMasquerade Omr <i>value</i>	AHB
Set PreserveCnames QuarantineJunk Rbl <i>value</i>	AHB
Set Rblhandling ReceivedForHdr RecipientCheck <i>value</i>	AHB
Set RewriteAddrFull Security SenderCheck <i>value</i>	AHB
Set SenderIsAuth SenderIsValidRecipient SmtPAuth <i>value</i>	AHB
Set Spf UceBlacklist UceSuspectlist UceWhitelist <i>value</i>	AHB
Set UceWhitelistIp UceWhitelistTo <i>value</i>	AHB
Set "(key=ucelist)(list=whitelist)(type=mh)" <i>value</i>	AHB
TestRblHost <i>hostname IPAddr</i>	A

SnmP

Add <i>label source community oid read write notify</i>	A
AddTrap <i>host community</i>	A
Count	AB
CountTrap	AB
Delete <i>label</i>	A
DeleteTrap <i>host</i>	A
Get <i>parameter</i> (see Set parameters)	AB
List <i>pattern</i>	AB
ListTrap	AB
Set SysContact SysLocation <i>value</i>	A

Softreboot

A

Spf

Add <i>parameter domain/host</i>	A
Count <i>parameter pattern</i>	AB
Delete <i>parameter host</i>	A
Get <i>parameter</i>	AB
List <i>parameter pattern</i>	AB
Set <i>parameter setting</i>	A
Test IPAddr FROM HELO	A

Ssh

Get Port	AB
Set Port <i>portnum</i>	A

Sshkey

Add <i>user key</i>	AH DU
Count <i>user</i>	AH DB U
Delete <i>user key</i>	AH DU
List <i>user pattern</i>	AH DB U

Ssl

GetAuthRequired	A
GetCert <i>interface</i>	A
GetCsr <i>interface</i>	A
GetIntCA <i>interface</i>	A
GetMaxKeyLen	A
GetMinKeyLen	A
GetVersion	A
NewCert <i>interface</i>	A
SetAuthRequired <i>value</i>	A
SetCert <i>interface</i>	A
SetIntCA <i>interface</i>	A
SetMaxKeyLen <i>value</i>	A
SetMinKeyLen <i>value</i>	A
SetVersion " <i>version</i> "	A

Stat

Get * <i>statistic</i> (run Help Stat Get)	A
---	---

Parameters enclosed by [and] are optional.
Keywords separated by | are alternatives.

Roles:

A = Administrator ■ H = Helpdesk administrator ■ D = Domain administrator
B = Backup operator ■ U = User

For detailed information about these commands:

Telnet to your Mirapoint system, log in as an administrator, and type Help.

COMMAND QUICK REFERENCE

Storage

AddArray	A
AddBackupDisk	AB
AddSpare	A
Alarm	A
Arrays	A
Battery <i>action battnum</i>	A
CheckAdd	A
ConfigSan <i>logicalID flags</i>	A
Configure <i>logicalID</i>	A
CountPaths <i>pattern</i>	A
CountPathStates <i>pathID</i>	A
CountSan <i>pattern</i>	A
CountSanPort <i>portID pattern</i>	A
Delete <i>logicalID</i>	A
Disks	A
Get BbStatus BbWriteThru BbWriteThruThresh	A
Get CheckFs Controller DiskVendor IdeCache	A
Get PortWwn RebuildRate StoreType	A
GetNas	A
GetPort <i>portID parameter</i>	A
ListBackupDisk	AB
ListPaths <i>pattern</i>	A
ListPathStates <i>pathID start count</i>	A
ListSan <i>pattern</i>	A
RemoveBackupDisk	AB
Scan	A
Set BbWriteThru BbWriteThruThresh CheckFs <i>value</i>	A
Set IdeCache RebuildRate <i>value</i>	A
Space	A

Trustedadmin

Add <i>address</i>	A
Count	AB
Delete <i>address</i>	A
List <i>pattern</i>	AB

Trustedhost

Add <i>type host-spec arg</i>	A
Count <i>type pattern</i>	AHB
CountTypes <i>pattern</i>	AHB
Delete <i>type host-spec</i>	A
List <i>type pattern</i>	AHB
ListTypes <i>pattern</i>	AHB

Uce

Add <i>block</i>	A
AddException <i>scope type address</i>	AH DU
Count	AB
CountException <i>scope type address</i>	AH DU
Delete <i>block</i>	A
DeleteException <i>scope type address</i>	AH DU
ExportExceptions <i>scope</i>	AH D
GetOption <i>option scope</i>	A
ImportExceptions <i>scope</i>	AH D
JunkMailSummaries <i>action</i>	A
List <i>pattern</i>	AB
ListException <i>scope type address</i>	AH DU
RemoveRuleGroup <i>rulegroup</i>	A
Report <i>type content</i>	A
SetOption <i>option scope setting</i>	A
Update <i>rulegroup</i>	A
Version	A

Update

Install <i>update-URL</i>	A
List	A
Uninstall <i>update-name</i>	A

Url

Add <i>class:instance description URL options</i>	AH D
Count <i>pattern</i>	AH DB
Delete <i>class:instance</i>	AH D
List <i>pattern</i>	AH DB

Parameters enclosed by [and] are optional.
Keywords separated by | are alternatives.

Roles:

A = Administrator ■ H = Helpdesk administrator ■ D = Domain administrator
B = Backup operator ■ U = User

For detailed information about these commands:

Telnet to your Mirapoint system, log in as an administrator, and type Help.

COMMAND QUICK REFERENCE

User

Add <i>username passarg fullname</i>	AHD
Count <i>pattern</i>	AHDB
Delete <i>username</i>	AHD
Get <i>parameter username</i> (see Set parameters)	AHDBU
List <i>pattern</i>	AHDB
Rename <i>login newlogin</i>	A
Set Auth CryptPass <i>username value</i>	AHDU
Set DeliveryAddress EncodedPass <i>username value</i>	AHDU
Set FullName JmmPrefs <i>username value</i>	AHDU
Set JunkmailSummary <i>username value</i>	AHDU
Set JunkmailSummaryEmptyLogs <i>username value</i>	AHDU
Set Login Pass WmAddrBook <i>username value</i>	AHDU
Set WmDictionary WmPrefs <i>username value</i>	AHDU

Version AHDBU

Webmail

Get <i>parameter</i> (see Set parameters)	AB
Set MaxNumRecips MaxMsgRate MaxRecipRate <i>value</i>	A
Set Timeout Omr <i>value</i>	A

Wordlist

Count <i>pattern</i>	AHDB
Delete <i>listname</i>	AHD
Export <i>listname</i>	AHDB
Import <i>listname wordlist</i>	AHD
List <i>pattern</i>	AHDB

Parameters enclosed by [and] are optional.

Keywords separated by | are alternatives.

Roles:

A = Administrator ■ H = Helpdesk administrator ■ D = Domain administrator

B = Backup operator ■ U = User

For detailed information about these commands:

Telnet to your Mirapoint system, log in as an administrator, and type Help.

